

RLC-830A-IP-Camera-Specifications		
	Model	RLC-830A
Video & Audio	Image Sensor	1/2.7"CMOS Sensor
	Video Resolution	3840 x 2160 (8.0 Megapixels) at 25 frames/sec
	Lens	f=4mm, fixed; f=1.6
	Video Format	H.265
	Field of View	Horizontal: 88°
		Vertical: 46°
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 30 Meters(LED: 2pcs/850nm)
	Color Night Vision	Spotlight: 2pcs/6500K/450 Lumens
Power	Audio	Two-way audio
	PoE	IEEE 802.3af, 48V active
Interface	DC Power	DC 12.0 V ~ 1 A, < 12 W
	Power	DC Power port
	System	Reset button
	Ethernet	1*10M/ 100Mbps RJ45
	Storage	Micro SD card slot (max. 256GB)
	Audio	Built-in microphone and speaker
Pan & Tilt	Pan &Tilt	Pan: 355°, Tilt: 0°~90°
	Pan Speed	12°-90°/s (The speed can be set.)
	Tilt Speed	8°-60°/s (The speed can be set.)
	Preset	32
	Auto Tracking	Available
Software Features	Frame Rate	Mainstream: 2fps - 25fps (Default: 25fps)
		Substream: 4fps - 15fps (Default: 10fps)
	Code Rate	Mainstream: 4096Kbps -8192Kbps (default: 6144Kbps)
		Substream: 64Kbps -512Kbps (default: 256Kbps)
	Compatible Browsers	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/ person detection/ vehicle detection/ pet detection
	Record Mode	Motion activated recording (default); scheduled recording; recording 24/7
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Maximum User Access	20 users (1 admin account and 19 user accounts); 12 simultaneous video streams (10 substreams and 2 mainstreams)
Working Environment	Work with	Google Assistant
	Temperature	Operating Temperature: -10°C~+50°C (14°F~122°F)
	Humidity	Operating Humidity: 10% ~ 90%
Size & Weight	Waterproof	IP65
	Dimension	228*110*147mm
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/
	Weight	1.2KG